

Mediant™ 3000 VoIP Media Gateway



- Deliver competitive, complete, best-of-breed media gateway functionality, featuring highest voice quality
- Build Voice over Packet (VoP) networks based on advanced media gateway technology
- Use as a medium-sized media gateway designed for converged wireless, wireline, cable, broadband access and fixed-mobile-convergence VoIP networks on a single media gateway platform
- Connect to high density, cost effective SONET/SDH PSTN interface
- Integrate 3G and 2G packet-enabled media gateway functionality into end-to-end system solution
- Meet the needs for VoIP Trunking, IP Centrex, and VoIP Access Gateway markets with a cost-effective media gateway
- Deploy globally with a rich offering of PSTN interfaces and signaling
- React quickly to dynamic market requirements

The **Mediant™ 3000** Media Gateway enables Network Equipment Providers (NEPs) and System Integrators (SIs) to offer Service Providers a compact media gateway solution targeted towards mid-sized carrier environment. Supporting 480 to 2,016 Low-Bit-Rate voice channels with OC-3/STM-1 PSTN interfaces, the Mediant 3000 addresses mid-density wireline, wireless, cable, broadband access and fixed-mobile-convergence applications. Building on AudioCodes' experience in the VoIP market, the Mediant 3000 supports a rich variety of VoIP vocoders, standards-compliant signaling and call control, state of the art Echo Cancellation, T.38 fax transmission and integrated SIGTRAN-compliant Signaling Gateway interworking. At a height of only 2U, the Mediant 3000 platform requires only minimal rack space. The Mediant 3000 is based on VolPerfect™ architecture, AudioCodes' underlying best-of-breed core media gateway technology for all of its products.

DEPLOY A RIGHT-SIZED SOLUTION

The Mediant 3000 provides a right-sized media gateway solution for mid-sized carrier networks. The small footprint of the Mediant 3000 Media Gateway is especially attractive for central office locations where space is at a premium. The Mediant 3000 provides PSTN and IP interfaces on a standard basis. In future releases, the Mediant 3000 will offer an optional 1+1 blade redundancy configuration as well.

FACILITATE FLEXIBLE DEPLOYMENT

The Mediant 3000 VoP Gateway system immediately addresses international opportunities that utilize a myriad of legacy circuit-switched infrastructure features and functionalities. The Mediant 3000 can communicate with PSTN (TDM), IP or IP Radio Access Network, centralized Mobile Switching Center (MSC) servers to enable complete 2G and 3G enterprise solutions. The Mediant 3000 allows superior deployment flexibility for these solutions which include Softswitches, Cable Call Management Systems (CMS), Media Terminal Adaptors (MTAs) PacketCable solutions, Broadband Wireless Local Loop (WLL) and Base Stations (WiFi, WiMax). The Mediant 3000 extends the flexibility of the Mediant Media Gateway family with additional OC-3c/STM1 deployment options.

MEDIANT 3000 FEATURES

- Designed for NEBS Level 3
- Field-proven, high voice quality
- SONET/SDH PSTN interfaces
- Wide support of PSTN protocol termination
- SIGTRAN Backhauling (SS7: M2UA/M3UA, PRI: IUA);
- SS7 and TDM peer-to-peer tunneling over IP
- Easy connectivity with emerging VoIP networks
- Packet telephony standards-compliant
- UMTS/ (Release 5 and IMS)-compliant version available
- CDMA compliant version available
- GSM compliant version available
- Supports PacketCable Standards
- Flexible deployment options
- Small footprint

AudioCodes Voice Network Products for Wireline, Wireless, Cable and Converged Applications

Mediant™ 3000

SPECIFICATIONS

Capabilities

Capacity	Up to 2,016 channels in 1+0 configuration Up to 2,016 channels in 1+1 configuration ¹
Voice Coders	• VoIP: G.711, G.723.1, G.726/7, G.729A/B • GSM/UMTS: GSM-FR, AMR (8 rates) & VoIP • CDMA: EVRC ³ QCELP 8k ¹ , QCELP 13k ¹ & VoIP: • CABLE: G.711, G.726/7, G.723.1, G.728 ^{1,3} , G.729E ³ G.729A/B Independent dynamic vocoder selection per channel (within each group)
Echo Cancellation	G.165 and G.168 compliant
Fax Support	T.38 (IP) compliant Group 3 fax relay and fax bypass (automatic fallback to G.711)
DTMF	Packet side or PSTN side detection and generation, RFC 2833 compliant
Voice over Packet Capabilities	Call progress tones, VAD, CNG, Dynamic programmable jitter buffer, DTMF detection and generation

Signaling

PSTN	ISDN PRI, CAS, MFC-R2, MF-R1 Interworking
SIGTRAN	ISDN-IUA/SCTP SS7- M2UA/SCTP, M3UA/SCTP SS7 and TDM Tunneling using M2UA over SCTP/IP
IP Transport	IETF RFC 3550, RFC 3551 RTP/IP Transport, TCP, UDP CDMA: IETF RFC 2658 and RFC 3558 RTP/UDP/IP
Control Protocols	MGCP (RFC 3435), MEGACO (H.248, RFC 3015), SIP (RFC 3261) ¹ IMS Mn - TS 29.332
Security	• IPSEC ³ – for control protocols and for Management Interfaces • HTTPS, SRTP ¹

Maintenance

Management	Element Management System, SNMP v2
Maintainability	All shelf modules are hot swappable, including boards, power supplies, fans
Redundancy Scheme	Power supply,fans: N+1 load shared Media Gateway blades (including PSTN interfaces): 1+1 ^{1,2} Optical Interfaces (PSTN): 1+1, APS protected

Hardware Specifications

Interfaces	PSTN: OC-3 or STM-1 APS optical links IP: Dual Redundant 100/1000 BASE-T Ethernet ports
Enclosure	4-slot, 2U cPCI chassis
Dimensions (HxWxD)	88 mm x 482.6 mm x 296.8 mm
Weight	Approx. 35.27 lbs. (16 kgs.), fully loaded
Mounting	Per EIA Standard RS-310-C in 19-inch rack specification
Power	48 V DC Dual Feed, with up to 2 DC Power modules
Cooling	Replaceable fan trays & filters

Regulatory Compliance

Telecommunication Standards	FCC part 68, TBR4 and TBR13
Safety and EMC Standards	• UL60950 • FCC part 15 Class A • CE Mark (EN55022 Class A,EN60950, EN55024, EN300 386)
Environmental	NEBS Level 3: GR-63-Core, GR-1089-Core, Type 1 & 3, ETS300 019

¹ Future releases

² Initially available in a 1+0 Media Gateway board configuration

³ Reduced channel capacity

ABOUT AUDIOCODES

AudioCodes Ltd. (NASDAQ: AUCD) enables the new voice infrastructure by providing innovative, reliable and cost-effective Voice over Packet technology and Voice Network products to OEMs, network equipment providers and system integrators. AudioCodes provides its customers and partners with a diverse range of flexible, comprehensive media gateway and media processing technologies, based on VoIPerfect™ – AudioCodes' underlying, best-of-breed, core media gateway architecture. The company is a market leader in voice compression technology and is a key originator of the ITU G.723.1 standard for the emerging Voice over IP market. AudioCodes voice network products feature media gateway and media server platforms for packet-based applications in the converged, wireline, wireless, broadband access, and enhanced voice services markets. AudioCodes enabling technology products include VoIP and CTI communication boards, VoIP media gateway processors and modules, and CPE devices. AudioCodes' headquarters and R&D facilities are located in Israel with an R&D extension in the U.S. Other AudioCodes' offices are located in Europe, the Far East, and Latin America.

International Headquarters

1 Hayarden Street, Airport City
Lod, Israel 70151
Tel: +972-3-976-4000
Fax: +972-3-976-4040

US Headquarters

2099 Gateway Place, Suite 500
San Jose, CA 95110
Tel: +1-408-441-1175
Fax: +1-408-451-9520

info@audiocodes.com

www.audiocodes.com

© 2005 AudioCodes Ltd. All rights reserved. AC, AudioCoded, AudioCodes logo, AudioCodes, IPmedia, Mediant, MediaPack, MP-MLQ, NetCoder, Stretto, TrunkPack, VoicePacketizer and VoIPerfect are trademarks or registered trademarks of AudioCodes Ltd. All other marks are the property of their respective owners. The information and specifications in this document and the product(s) are subject to change without notice.

Ref. #LTRT-38401 08.05 V.1

